FACOT CHEMICALS S.r.l.
Via Crema, 44 - 26010 Capralba (CR) – Italy
Tel. +39 0373 450642 - Fax +39 0373 450751
info@facot.it - www.facot.it

Reg. Imp. di Cremona n. 00944000199
P.IVA e Cod. Fiscale 00944000199
Capitale sociale i.v. € 100.000,00
pec: facot@messaggipec.it

PRODOTTI CHIMICI E TECNICI — CHEMICAL AND TECHNICAL PRODUCTS — CHEMISTRY IN ACTION

PULITENE DETERGENTE

DESCRIPTION:
Special solvent in a bottle for the cleaning of polyethylene, polypropylene and PVC to be welded.

INSTRUCTIONS FOR USE:
Pour a little quantity of product on a cloth and wipe the piece to be welded in order to eliminate any possible impurity that may affect the welding. Wait a few seconds the product has evaporated than weld as asual.

TECHNICAL DATA:

Appearance	colorless liquid
Smell	characteristic
pH at @ 20 °C	not applicable
Boiling point	~ 75 °C
Flash point	-4 °C
Fusion point	-84 °C
Relative density	0,900 ± 0,050 g/cm³
Solubility in water	partially soluble (~ 8 %)
Lipid solubility	complete
Auto-ignition temperature	425 °C
Vapour pressure at @ 20 °C	~ 101 hPa
VOC	100%

PACKAGING:
Bottle 750 ml with sprayer, boxes with 6 pieces.

INGREDIENTS:
Ethyl Acetate.

Last update: 20.01.2017